PATENT

DOCKET NO.: LCOM-0656 **Application No.:** 10/773,947

Preliminary Amendment - First Action Not Yet Received

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Canceled)

2. (New) A radial power divider/combiner comprising:

a first antenna disposed at the center of the substrate;

a plurality of waveguides, each of which extends along a respective direction between the center of the substrate and the periphery thereof; and

a plurality of second antennas, each said second antenna disposed near a respective end of a respective one of the waveguides.

- 3. (New) The radial power divider/combiner of claim 2, wherein the first antenna extends in a first direction from the substrate and the second antennas extend in the first direction from the substrate.
- 4. (New) The radial power divider/combiner of claim 2, further comprising a cover secured to the substrate, wherein the first antenna extends in a first direction from the first substrate and the second antennas extend in a second direction from the cover.
- 5. (New) The radial power divider/combiner of claim 4, wherein the substrate and the cover define an interior region of the divider/combiner, and wherein the first antenna and the second antennas extend into the interior region of the divider/combiner.
- 6. (New) The radial power divider/combiner of claim 2, wherein the waveguides comprise respective grooves in the substrate.
- 7. (New) The radial power divider/combiner of claim 2, wherein the first antenna is adapted to receive a signal and transmit the received signal through the waveguides to the second antennas.

DOCKET NO.: LCOM-0656 PATENT

Application No.: 10/773,947

Preliminary Amendment - First Action Not Yet Received

8. (New) The radial power divider/combiner of claim 2, wherein each of the second antennas is adapted to receive a respective signal transmitted through the respective one of the waveguides.

- 9. (New) The radial power divider/combiner of claim 8, wherein each of the second antennas is electrically coupled to a respective amplifier, and is adapted to provide the respective received signal to the respective amplifier.
- 10. (New) The radial power divider/combiner of claim 2, wherein each of the second antennas is adapted to transmit a respective signal through the waveguides to the first antenna.
- 11. (New) The radial power divider/combiner of claim 10, wherein each of the second antennas is electrically coupled to a respective amplifier, and is adapted to receive a respective signal from the respective amplifier.
- 12. (New) A radial power divider-combiner comprising:
 - a radial power divider comprising:
 - a first substrate having a center and a periphery;
 - a first antenna disposed at the center of the first substrate;
- a first plurality of waveguides, each of which extends along a respective direction between the center of the first substrate to the periphery thereof; and
- a plurality of second antennas, each said second antenna disposed near a respective end of a respective one of the first plurality of waveguides; and
 - a radial power combiner comprising:
 - a second substrate having a center and a periphery;
 - a third antenna disposed at the center of the second substrate;
 - a second plurality of waveguides, each of which extends along a respective
- direction between the center of the second substrate to the periphery thereof; and
- a plurality of fourth antennas, each said fourth antenna disposed near a respective end of a respective one of the second plurality of waveguides.

DOCKET NO.: LCOM-0656

Application No.: 10/773,947

Preliminary Amendment - First Action Not Yet Received

13. (New) The radial power divider-combiner of claim 12, further comprising a plurality of power amplifiers, each said power amplifier electrically coupled between a respective one of

PATENT

the second antennas and a respective one of the fourth antennas.

14. (New) The radial power divider-combiner of claim 12, wherein the first antenna is

adapted to receive a signal and transmit the received signal through the first plurality of

waveguides to the second antennas.

15. (New) The radial power divider-combiner of claim 12, wherein each of the second

antennas is adapted to receive a respective signal transmitted through the respective one of

the first plurality of waveguides.

16. (New) The radial power divider-combiner of claim 13, wherein each of the second

antennas is adapted to receive a respective signal transmitted through the respective one of

the first plurality of waveguides, and to provide the respective received signal to the

respective amplifier.

17. (New) The radial power divider-combiner of claim 12, wherein each of the fourth

antennas is adapted to transmit a respective signal through the respective one of the second

plurality of waveguides to the third antenna.

18. (New) The radial power divider-combiner of claim 13, wherein each of the fourth

antennas is adapted to receive a respective signal from the respective amplifier and to

transmit the respective signal through the respective one of the second plurality of

waveguides to the third antenna.

Application No.: 10/773,947

Preliminary Amendment - First Action Not Yet Received

19. (New) A solid-state power-amplifier module comprising:

a radial power divider comprising:

- a first substrate having a center and a periphery;
- a first antenna disposed at the center of the first substrate;
- a first plurality of waveguides, each of which extends along a respective direction between the center of the first substrate to the periphery thereof; and
- a plurality of second antennas, each said second antenna disposed near a respective end of a respective one of the first plurality of waveguides; and
 - a radial power combiner comprising:
 - a second substrate having a center and a periphery;
 - a third antenna disposed at the center of the second substrate;
 - a second plurality of waveguides, each of which extends along a respective

direction between the center of the second substrate to the periphery thereof; and

- a plurality of fourth antennas, each said fourth antenna disposed near a respective end of a respective one of the second plurality of waveguides;
 - a signal generator that provides an input signal to the first antenna; and
 - a signal receiver that receives an amplified signal from the third antenna.